

## Cleaning and maintenance



















The flooring has a strong protective finish which makes cleaning and maintenance easy. An occasional wipe with a damp cloth or mop will take care of your day to day care and maintenance.

## Installation






For best results professional installation is recommended. Before installation subfloors must be permanently dry, smooth, level and of sound construction

## Technical Specification

FLOORINK meets the requirements of EN649

		<b>Industrial</b>
	Total thickness	EN 428 2.2 mm
	Thickness wear layer	EN 429 0.7 mm
	Collection size	42
	Commercial very heavy	EN 685 Class 34
	Industrial heavy	EN 685 Class 43
	Roll width	EN 426 2.00 m
	Roll length	EN 426 ± 25 m
	Total weight	EN 430 2.85 kg/m <sup>2</sup>
	Dimension stability	EN 434 < 0.1 %
	Indentation residual	EN 433 0.05 mm*
	Abrasion resistance	EN 660-1 Group T
	Castor chair continuous use	EN 425 No effect
	Light fastness	ISO 105-B02 ≥ 6
	Flexibility	EN 435 ø 10 mm
	Resistance to chemicals	EN 423 Very good
	Slip resistance	DIN 51130 R10
	Suitable for floor heating	yes**
	Acoustical impact noise reduction	EN ISO 717-2

**Industrial** meets the requirements of EN 14041

	Reaction to fire	EN 13501-1 B <sub>fl</sub> -s <sub>1</sub>
	Slip resistance	EN 13893 DS: ≥ 0.30
	Body voltage	EN 1815 ≤ 2 kV
	Electrical resistance	EN 1081
	Thermal conductivity	EN 12524 0.25 W/m.K

\* Typical value

\*\* Temperature < 30 °C